## Dell EMC PowerEdge R250

# **D**&LLTechnologies

1 pour los

**Spec Sheet** 

### Deliver the value of data

The Dell EMC PowerEdge R250 affordably addresses common business workloads while delivering compute with an entry-level 1U rack server.

#### Your Innovation Engine for businesses of all sizes

The Dell EMC PowerEdge R250, powered by Intel<sup>®</sup> Xeon<sup>®</sup> E-2300 processors, delivers powerful compute for common business applications and streamlines productivity. It supports 3200 MT/s DDR4 speeds and 32 GB DIMMs, up to 128 GB for memory intensive workloads. In addition, to address substantial throughput improvements, the PowerEdge R250 supports PCIe Gen 4 and offers enhanced thermal efficiency to support increasing power and thermal requirements. This makes the PowerEdge R250 an rack ideal server for buisness critical workloads, cloud infrastructure, and point of sale transactions in a 1U form factor, for small to midsized businesses, inside and outside of the data center.

#### Increase efficiency and accelerate operations with autonomous collaboration

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools

#### Protect your data assets and infrastructure with proactive resilience

The Dell EMC PowerEdge R250 server is designed with a cyber-resilient architecture, integrating security deeply into every phase in the lifecycle, from design to retirement.

- Operate your workloads on a secure platform anchored by cryptographically trusted booting and silicon root of trust
- Maintain server firmware safety with digitally signed firmware packages
- Prevent unauthorized configuration or firmware change with system lockdown
- Securely and quickly wipe all data from storage media, including hard drives, SSDs and system memory with System Erase

#### PowerEdge R250

The Dell EMC PowerEdge R250 offers streamlined productivity, highspeed memory and capacity, powerful compute to address common business applications. Ideal for:

- Small midsized businesses
- Remote office/branch office
- Collaboration and sharing
- Mail/messaging and file/print

Feature	Technical Specifications	
Processor	One Intel Xeon E-2300 series processor with up to 8 cores	
Memory	Four DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s	
	Supports unregistered ECC DDR4 DIMMs only	
	Note: For Pentium processor, the maximum memory speed is 2666 MT/s.	
Storage controllers	<ul> <li>Internal controllers: PERC H345, H355, H755, HBA355i, S150</li> </ul>	
0	<ul> <li>Internal Boot: Internal Dual SD Module or USB or Boot Optimized Storage Subsystem (BOSS-S1): HWRAID 2 x M.2 SSDs</li> </ul>	
	<ul> <li>External HBAs (non-RAID): HBA355e</li> </ul>	
Drive bays	Front bays:	
Dive bays	<ul> <li>Up to 4 x 3.5-inch hot swap SAS/SATA (HDD/SSD) max 30.72 TB</li> </ul>	
	<ul> <li>Up to 2 x 3.5-inch cabled SAS/SATA (HDD/SSD) max 15.36 TB</li> </ul>	
	<ul> <li>Up to 4 x 3.5-inch cabled SAS/SATA (HDD/SSD) max 30.72 TB</li> </ul>	
Power supplies	450W Bronze 100-240 VAC, cabled	
Power supplies	<ul> <li>450W Platinum 100-240 VAC, cabled</li> <li>450W Platinum 100-240 VAC, cabled</li> </ul>	
Cooling options		
Cooling options	Air cooling	
Fans	Up to four cabled fans	
Dimension	• Height: 42.8 mm (1.68 inches)	
	• Width: 482 mm (18.97 inches)	
	Depth: 598.64 mm (23.56 inches) with bezel	
	585 mm (23.03 inches) without bezel	
Form Factor	1U rack server	
Embedded management	• iDRAC9	
	iDRAC Direct	
	iDRAC RESTful API with Redfish	
	iDRAC Service Module	
Bezel	Optional bezel or security bezel	
OpenManage Software	OpenManage Enterprise	
	OpenManage Power Manager plugin	
	OpenManage SupportAssist plugin	
	OpenManage Update Manager plugin	
Mobility	OpenManage Mobile	
Integrations and Connections	OpenManage Integrations	OpenManage Connections
	BMC Truesight	IBM Tivoli Netcool/OMNIbus
		IBM Tivoli Network Manager IP Edition
	Microsoft System Center     Red Hat Ansible Modules	Micro Focus Operations Manager
	VMware vCenter and vRealize Operations Manager	Nagios Core
0 11		Nagios XI
Security	Cryptographically signed firmware	
	Secure Boot	
	Secure Erase	
	Silicon Root of Trust	
	System Lockdown (requires iDRAC9 Enterprise or Datacenter)	
	• TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat	
Embedded NIC	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2	
Embedded NIC GPU options	• TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat	
	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2	
GPU options	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2 Not supported	ionZ
GPU options	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2 Not supported Front Ports	ionZ Rear Ports
GPU options	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2 Not supported Front Ports     1 x USB 2.0	Rear Ports • 1 x USB 2.0
GPU options	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2 Not supported Front Ports     1 x USB 2.0	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port
GPU options	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0
GPU options Ports	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2 Not supported Front Ports     1 x USB 2.0     1 x iDRAC Direct (Micro-AB USB) port Internal Ports     1 x USB 3.0 (optional) 2 PCIe slots:	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options Ports	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCle slots: <ul> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options Ports PCIe	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCle slots: <ul> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options Ports	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nation</li> <li>Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCle slots: <ul> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> <li>Canonical Ubuntu Server LTS</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options Ports PCIe	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nat Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCIe slots: <ul> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> <li>Canonical Ubuntu Server LTS</li> <li>Citrix Hypervisor</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options Ports PCIe	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nation</li> <li>Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCle slots: <ul> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> <li>Canonical Ubuntu Server LTS</li> <li>Citrix Hypervisor</li> <li>Microsoft Windows Server with Hyper-V</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options Ports PCIe	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nation</li> <li>Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCIe slots: <ul> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> <li>Canonical Ubuntu Server LTS</li> <li>Citrix Hypervisor</li> <li>Microsoft Windows Server with Hyper-V</li> <li>Red Hat Enterprise Linux</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA
GPU options Ports PCIe	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nation</li> <li>Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul> </li> <li>Internal Ports <ul> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCle slots: <ul> <li>1 x8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> <li>Canonical Ubuntu Server LTS</li> <li>Citrix Hypervisor</li> <li>Microsoft Windows Server with Hyper-V</li> <li>Red Hat Enterprise Linux</li> <li>SUSE Linux Enterprise Serveri</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethernet port • 1 x USB 3.0 • 1 x VGA • 1 x Serial port
GPU options Ports PCIe	<ul> <li>TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China Nation</li> <li>Onboard LOM 1GbE x2</li> <li>Not supported</li> <li>Front Ports <ul> <li>1 x USB 2.0</li> <li>1 x USB 2.0</li> <li>1 x USB 3.0 (optional)</li> </ul> </li> <li>2 PCIe slots: <ul> <li>1 x 8 Gen4 (x16 connector) low profile, half length</li> <li>1 x8 Gen4 (x8 connector) low profile, half length</li> <li>Canonical Ubuntu Server LTS</li> <li>Citrix Hypervisor</li> <li>Microsoft Windows Server with Hyper-V</li> <li>Red Hat Enterprise Linux</li> <li>SUSE Linux Enterprise Serveri</li> </ul> </li> </ul>	Rear Ports • 1 x USB 2.0 • 1 x iDRAC ethemet port • 1 x USB 3.0 • 1 x VGA • 1 x Serial port

Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit Dell.com/ServiceDescriptions.

#### **APEX Flex on Demand**

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm.

#### Discover more about PowerEdge servers



Learn more about our

PowerEdge servers



Learn more about our systems management solutions







Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for Sales or Support

**D&LL**Technologies

© 2021 Dell Inc. or its subsidiaries. All Rights Reserved. Dell, EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.